



DIN Rail Decoupling Inductor



- For decoupling of spark gaps and MOVs
- Allows correct coordination of different SPD technologies
- Tunnel terminals accepts large cable size



Part Number	DDI35	DDI63
Article Number	-	700475
Max Continuous Operating Voltage (Uc)	500 VAC 200 VDC	
Rated Load Current (IL)	35 A	63 A
Frequency	0 – 60 Hz	
Inductance	8 μ H	15 μ H
Loop Resistance	4.5 m Ω	1.7 m Ω
Connection, Solid	35 mm ² Max	
Connection, Stranded	25 mm ² Max	
Status Indication	LED	
Enclosure Material	UL [®] 94V-0 Thermoplastic	
Enclosure Rating	IP 20 NEMA [®] -1	
Mounting	35 mm top hat DIN rail	
Humidity	0 – 90 % RH	
Temperature	-35 to 55 °C	
Module Width	2 M	4 M
Depth (D)	70 mm	
Height (H)	90 mm	
Width (W)	36 mm	72 mm
Unit Weight	0.2 kg	0.7 kg

NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.