


DINLINE Alarm Relay



- Used with TDF products where alarm contacts are required for remote signaling



Part Number	DAR275V
Article Number	700900
Nominal System Voltage (Un)	100 - 240 VAC 20 - 110 VDC
Max Continuous Operating Voltage (Uc)	275 V
Max Operating Current	20 mA
Stand-off Voltage	275 V
Status Indication	LED Change-over contact
System Compatibility	TN-C TN-C-S TN-S TT
Trip Threshold	300 A 8/20 μ s
Connection, Stranded	1 - 6 mm ²
Humidity	0 - 90 % RH
Temperature	-35 to 55 °C
Enclosure Material	UL [®] 94V-0 Thermoplastic
Enclosure Rating	IP 20 NEMA [®] -1
Module Width	2 M
Mounting	35 mm top hat DIN rail
Unit Weight	0.2 kg
Depth (D)	68 mm
Height (H)	90 mm
Width (W)	36 mm

NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.