


Potential Equalization Clamp



- High peak current capability provides long service life
- Weatherproof enclosure is suitable for direct burial
- The PEC100 is ATEX approved and suitable for use in potentially explosive atmospheres



Part Number	PEC100	PEC150
Article Number	702900	702901
Spark-Over Voltage @ 100 V/s	350 V	800 V
Max Discharge Current (I _{max})	100 kA 8/20 µs	150 kA 8/20 µs
Technology	Gas Discharge Tube (GDT)	
Insulation Resistance	1 GΩ Min	
Capacitance	15 pF Max	
Voltage Protection Level (U _p)	800 V @ 1,000 V/µs	1,500 V @ 1,000 V/µs
Impulse Current (I _{imp})	25 kA 10/350 µs	50 kA 10/350 µs
Lead Length	450 mm	
Lead Size	16 mm ²	
Enclosure Rating	IP 66 IP 67	
Temperature	-30 to 70 °C	
Diameter 1 (Ø1)	28.0 mm	42.4 mm
Diameter 2 (Ø2)	16.30 mm	17.45 mm
Length (L)	953 mm	914 mm
Unit Weight	0.5 kg	0.7 kg
Complies With	IEC@ 61643-1 Class I, Class II IEC@ 62561-3	
Certifications	ATEX CE IECEX	-

Spark-over voltage has a tolerance of +/- 20%.

IEC is a registered trademark of the International Electrotechnical Commission.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.