


Surge Counter, Digital Display



- Records time and date of transient surge events
- Resettable counter
- Snap on, hall effect transducer



Part Number	DSCL2
Trip Threshold	100 A 8/20 μ s
Status Indication	LED
Connection, Stranded	50 mm ² Max
Lead Length	51 cm
Enclosure Material	UL [®] 94V-0 Thermoplastic
Enclosure Rating	IP 20 NEMA [®] -1
Mounting	35 mm top hat DIN rail
Temperature	-20 to 70 °C
Module Width	2 M
Depth (D)	68 mm
Height (H)	90 mm
Width (W)	36 mm
Unit Weight	190 g

NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.